

Chargeur triphasé rétrofit X3-fit-8.0e

Kod Electriquo: 99893



UWAGA: Zdjęcie poglądowe dla całej rodziny produktów.

Dane techniczne:

- Pouvoir **8000W**
- Tension [V] **sieci 400/230;380/220 baterii 160-800**
- Classe de protection IP **IP65**
- Dimensions **457x654x228**
- Waga **38.00**
- Pouvoir **8000W**
- Tension [V] **sieci 400/230;380/220 baterii 160-800**
- Classe de protection IP **IP65**
- Dimensions **457x654x228**
- Waga **38.00**

Produisez de l'énergie à partir de panneaux solaires pendant la journée. Lorsque la charge de base est satisfaite, le système intelligent SolaX X3 Retro Fit redirige l'excédent d'énergie vers la batterie pour une utilisation ultérieure. Vous pouvez ainsi optimiser l'énergie produite. En cas de panne de courant, le X3 Retro Fit renvoie l'énergie stockée chez vous, vous assurant ainsi de ne jamais être laissé dans le noir, même en cas de panne de courant.

Rendement élevé : max. 96 %

Refroidissement naturel

Compatible avec les batteries haute tension

Protection contre les pannes de courant

Option de connexion à la batterie

Surveillance à distance

IP65



UWAGA: Zdjęcie poglądowe dla całej rodziny produktów.

	X3-Fit-8.0		X3-Fit-10.0	
	E Version	C Version	E Version	C Version
OUTPUT (AC)				
Nominal AC power [VA]	8000	8000	10000	10000
Max. apparent AC power [VA]	8000	8000	10000	10000
Nominal grid voltage(AC voltage range) [V]	400V/230VAC;380/220VAC			
Nominal grid frequency/range [Hz]	50/60			
Nominal AC current [A]	11.6	11.6	14.5	14.5
Max. AC current [A]	12.8	12.8	16.0	16.0
Displacement power factor	0.8 leading to 0.8 lagging			
THDI, rated power [%]	<3			
INPUT AC				
Max. apparent AC power[VA]	8000	8000	10000	10000
Max. AC current[A]	12.8	12.8	16.0	16.0
Nominal grid voltage(AC voltage range)[V]	400/230;380/220			
Nominal grid Frequency/range[Hz]	50/60			
OUTPUT DC (BATTERY)				
Battery voltage range [V]	160-800			
Max.continuous charge/discharge current [A]	35(0.5H)			
Communication interfaces	CAN/ RS485			
Reverse connect protection	YES			
EPS OUTPUT(WITH BATTERY)				
EPS MAX. continuous apparent power [VA]	8000	—	10000	—
EPS rated voltage[VAC],Frequency [Hz]	400/230;380/220 50/60	—	400/230;380/220 50/60	—
EPS MAX,continuous current [A]	11.6	—	14.5	—
EPS peak apparent power [VA] Duration [s]	10000 60	—	10000 60	—
Changeover time [s]	<1.5	—	<1.5	—
THDv, linear Load [%]	<2	—	<2	—
Changeover device	external	—	external	—
Three phases unbalanced	YES			
EFFICIENCY				
Max. Battery charge efficiency (GRID to BAT)	96.0			
Max. Battery discharge efficiency (BAT to AC)	96.5			
POWER CONSUMPTION				
Standby consumption (Night) [W]	50 in standby mode, 10 in idle mode			
SAFETY& PROTECTION				
Over/under voltage protection	Yes			
Monitoring ground fault protection	Yes			
Grid protection	Yes			
STANDARD				
Safety	IEC62477			
EMC	EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3			
Certification	VDE 0126-1-1 A1:2012 / VDE-AR-N 4105 / G98 / AS4777 / EN50549/ CEI 0-21			
ENVIRONMENT LIMIT				
Degree of protection(according to IEC60529)	IP65			
Operating temperature range [°C]	-20..... +60 (derating at +45)			

UWAGA: Zdjęcie poglądowe dla całej rodziny produktów.